



**Specification**

Product Description	4.3/10 Quick Male Compression Connector for 1/2" Normal Cable	Date: 2019.4.12
Part NO.	AFDF77-3	Ver. 2

UNIT: mm

[Installation instructions](#)



**Reference Standard**

**IEC60169-54**

**Electrical Performance**

Nominal Impedance (Ω)	50
Frequency Range	DC~6GHz
VSWR	≤1.15(0-3GHZ) ≤1.35(3-6GHZ)
VSWR(DTF)	≤1.05(0-3GHZ) ≤1.10(3-6GHZ)
PIM (dBc)	≤-160(2*43dBm)
Insertion Loss	≤0.1 √ F(GHz)
Insulation Resistance(MΩ/500VDC)	≥5000
Proof Voltage (V/AC)	≥2500
Contact Resistance (mΩ)	≅ 1.0 (Inner Conductor) ≅ 1.0 (Outer Conductor)

### Mechanical Performance

Interface Durability	500 Cycles
Nut Torque	5 N.m
(Nut) Whorl Pull	500 N
Tensile Force (Cable-Connector)	500 N
Torsion (Cable-Connector)	5N.m
Engagement Force	Typical 80N
Separation Force	Typical 60N
Weight	162.86g

### Material and Plating

Connector Parts	Material	Plating
Inner Conductor	Spring Copper	Ag 5μm
Outer Conductor	Brass	Copper-tin-zinc2μm
Nut	Brass	Copper-tin-zinc2μm
Insulator	TPX	
Gasket	Silicone Rubber	

### Environment

Temperature Range	-40°C~+85°C
Weather Standard	IEC60068 40/ 085/ 21
Thermal Shock	IEC60068-2-14-Na
Vibration	IEC60068-2-6-Fc
Shock	IEC60068-2-27
Waterproofing Standard	IP68
RoHS	Compliant(EU and China)

### Assembly

Inner conductor Installed and outer conductor Compressed.

Cable Supported	Cable Type Supported	Cable Supported	Cable Type Supported
Amphenol	AFY-50-12R	Andrew	LDF4-50A
Draka	RF1/2"-50	Andrew	HL4RPV-50A (Plenum)
Eupen	EC4-50	Andrew	AL4RPV-50 (Plenum) (Apply to 0-4.2GHz)
RFS	LCF12-50J	RFS	ICA12-50JPLW (Plenum)

NOTE: The technical specification contains proprietary information and such information may not be disclosed to others for any particular purpose or used for manufacturing purposes without written permission from Amphenol Fuyang.